

UNNATI EXIMP INTERNATIONAL

Delhi, Jaipur, Mumbai, Hyderabad, Coimbtore, Surat, Mathura, Amritsar

Web: www.glowelgroup.com. Email: unnati@glowelgroup.com



SPECIFICATIONS:-

- WITH STRONG STEEL BODY HAVING THICKNESS 25mm
- NO DAMAGE TO THE SURFACE
- APPLICATION SUITABLE FOR:GOLD, SILVER, BRASS, STEEL
 "COINS POLISHING WORK ALSO!"
 - AMERICAN DuPont ADHESIVE LAYERS FOR SAFETY AND LONGER INNER SHELF LIFE OF TUMBLER
- CAN GO UPTILL 60,000 -RPM,
 RESULTING INCREASE IN PRODUCTION CAPACITY IN LESSER WORKTIME
- DIRECT SPEED TO 1450/RPM (can opt for speed/time controller-" optionally"
- PROVIDED &SUITABLE WITH ZIRCONIUM MEDIA FOR HIGH END POLISH FINISH

MODELS	PROCESSING WEIGHT	POWER	VOLTAGE
GC-	UPTO 60 KGS	0.7-1.1	380V
JPV/T 60L		KW	3 PHASE MOTOR
GC-	UPTO 100 KGS	1.1	380V
JPV/T 100L		KW	3 PHASE MOTOR